

Two-color, high-luminance numeric displays


LA-621 AK Series

The LA-621 AK series are two-color, high-luminance numeric displays designed to be used in bright locations. Red, green and orange displays are possible.

●Features

- 1) Height of display : 15 mm.
- 2) Dimensions : 12.5 × 19 × 8 mm.
- 3) Common anode and common cathode configurations are available.
- 4) The package surface is coated black and the segments are milky white.
- 5) High luminance, clear display.
- 6) Red, green and orange displays are possible.


●External dimensions (Units: mm)



●Selection guide


Emitting color	Red / Green
Common	LA-621LMA
Anode	LA-621LMK
Cathode	

●Pin assignments




Pin No.	Function
1	Segment "e"
2	Segment "d"
3	Red Common
4	Segment "c"
5	Segment "D.P"
6	Segment "b"
7	Segment "a"
8	Green Common
9	Segment "g"
10	Segment "f"

● Internal circuit schematic (example of common cathode)



(example of common anode)



● Absolute maximum ratings (Ta = 25°C)

Parameter	Symbol	Red	Green	Unit
		LA-621LMA / LMK	LA-621LMA / LMK	
Power dissipation	P _D	1000	480	mW
Power dissipation	P _D / seg	125	60	mW
Forward current	I _F	50	20	mA
Peak forward current	I _{FP}	80*	60*	mA
Reverse voltage	V _R	3	3	V
Operating temperature	T _{opr}	-25~+75		°C
Storage temperature	T _{stg}	-30~+85		°C

* Pulse width 1ms duty 1 / 10

● Electrical and optical characteristics (Ta = 25°C)

Parameter	Symbol	Conditions	Red			Green			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Forward voltage	V _F	I _F =20mA	—	1.75	2.5	—	2.1	2.8	V
Reverse current	I _R	V _R =3V	—	—	10	—	—	10	μA
Peak wavelength	λ _P	I _F =20mA	—	660	—	—	563	—	nm
Spectral line half width	Δλ	I _F =20mA	—	25	—	—	40	—	nm

©Not designed for radiation resistance.

● Luminous intensity

Color	λ _P	Type	Min.	Typ.	Max.	Unit
Red	660	LA-621LMA	14	50	—	mcd
		LA-621LMK				
Green	563	LA-621LMA	9.0	25	—	mcd
		LA-621LMK				

Note: Measured at I_F = 20mA