

# SN54HC4002, SN74HC4002 DUAL 4-INPUT POSITIVE-NOR GATES

SCLS157

D2684, DECEMBER 1982—REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

## description

These devices contain two independent 4-input positive NOR gates. They perform the Boolean functions:

$$Y = \overline{A + B + C + D} \text{ or } Y = \overline{A} \cdot \overline{B} \cdot \overline{C} \cdot \overline{D}$$


in positive logic.

The SN54HC4002 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HC4002 is characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

FUNCTION TABLE

| INPUTS |   |   |   | OUTPUT |
|--------|---|---|---|--------|
| A      | B | C | D | Y      |
| H      | X | X | X | L      |
| X      | H | X | X | L      |
| X      | X | H | X | L      |
| X      | X | X | H | L      |
| L      | L | L | L | H      |


## logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54HC4002 . . . J PACKAGE  
SN74HC4002 . . . D OR N PACKAGE  
(TOP VIEW)




SN54HC4002 . . . FK PACKAGE  
(TOP VIEW)



NC—No internal connection

## logic diagram (positive logic)



PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

TEXAS  
INSTRUMENTS

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

Copyright © 1982, Texas Instruments Incorporated

**SN54HC4002, SN74HC4002**  
**DUAL 4-INPUT POSITIVE-NOR GATES**

**absolute maximum ratings over operating free-air temperature range†**

|                                                                             |                |
|-----------------------------------------------------------------------------|----------------|
| Supply voltage range, $V_{CC}$ .....                                        | -0.5 V to 7 V  |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ or $V_I > V_{CC}$ ) .....         | $\pm 20$ mA    |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ or $V_O > V_{CC}$ ) .....        | $\pm 20$ mA    |
| Continuous output current, $I_O$ ( $V_O = 0$ to $V_{CC}$ ) .....            | $\pm 25$ mA    |
| Continuous current through $V_{CC}$ or GND pins .....                       | $\pm 50$ mA    |
| Lead temperature 1,6 mm (1/16 in) from case for 60 s: FK or J package ..... | 300°C          |
| Lead temperature 1,6 mm (1/16 in) from case for 10 s: D or N package .....  | 260°C          |
| Storage temperature range .....                                             | -65°C to 150°C |

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

**recommended operating conditions**

|          |                                        | SN54HC4002       |      |          | SN74HC4002 |      |          | UNIT |
|----------|----------------------------------------|------------------|------|----------|------------|------|----------|------|
|          |                                        | MIN              | NOM  | MAX      | MIN        | NOM  | MAX      |      |
| $V_{CC}$ | Supply voltage                         | 2                | 5    | 6        | 2          | 5    | 6        | V    |
| $V_{IH}$ | High-level input voltage               | $V_{CC} = 2$ V   | 1.5  |          | 1.5        |      |          | V    |
|          |                                        | $V_{CC} = 4.5$ V | 3.15 |          | 3.15       |      |          |      |
|          |                                        | $V_{CC} = 6$ V   | 4.2  |          | 4.2        |      |          |      |
| $V_{IL}$ | Low-level input voltage                | $V_{CC} = 2$ V   | 0    | 0.3      | 0          | 0.3  |          | V    |
|          |                                        | $V_{CC} = 4.5$ V | 0    | 0.9      | 0          | 0.9  |          |      |
|          |                                        | $V_{CC} = 6$ V   | 0    | 1.2      | 0          | 1.2  |          |      |
| $V_I$    | Input voltage                          | 0                |      | $V_{CC}$ | 0          |      | $V_{CC}$ | V    |
| $V_O$    | Output voltage                         | 0                |      | $V_{CC}$ | 0          |      | $V_{CC}$ | V    |
| $t_t$    | Input transition (rise and fall) times | $V_{CC} = 2$ V   | 0    | 1000     | 0          | 1000 |          | ns   |
|          |                                        | $V_{CC} = 4.5$ V | 0    | 500      | 0          | 500  |          |      |
|          |                                        | $V_{CC} = 6$ V   | 0    | 400      | 0          | 400  |          |      |
| $T_A$    | Operating free-air temperature         | -55              |      | 125      | -40        |      | 85       | °C   |

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

| PARAMETER | TEST CONDITIONS                                         | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |           |           | SN54HC4002 |            | SN74HC4002 |            | UNIT          |
|-----------|---------------------------------------------------------|----------|--------------------------|-----------|-----------|------------|------------|------------|------------|---------------|
|           |                                                         |          | MIN                      | TYP       | MAX       | MIN        | MAX        | MIN        | MAX        |               |
| $V_{OH}$  | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OH} = -20 \mu\text{A}$ | 2 V      | 1.9                      | 1.998     |           | 1.9        |            | 1.9        | V          |               |
|           |                                                         | 4.5 V    | 4.4                      | 4.499     |           | 4.4        |            | 4.4        |            |               |
|           |                                                         | 6 V      | 5.9                      | 5.999     |           | 5.9        |            | 5.9        |            |               |
|           | 4.5 V                                                   | 3.98     | 4.30                     |           | 3.7       |            | 3.84       |            |            |               |
| $V_{OL}$  | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OL} = 20 \mu\text{A}$  | 2 V      |                          | 0.002     | 0.1       |            | 0.1        |            | 0.1        |               |
|           |                                                         | 4.5 V    |                          | 0.001     | 0.1       |            | 0.1        |            | 0.1        |               |
|           |                                                         | 6 V      |                          | 0.001     | 0.1       |            | 0.1        |            | 0.1        |               |
|           | 4.5 V                                                   |          | 0.17                     | 0.26      |           | 0.4        |            | 0.33       |            |               |
|           | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OL} = 5.2 \text{ mA}$  | 6 V      |                          | 0.15      | 0.26      |            | 0.4        |            | 0.33       |               |
| $I_I$     | $V_I = V_{CC}$ or 0                                     | 6 V      |                          | $\pm 0.1$ | $\pm 100$ |            | $\pm 1000$ |            | $\pm 1000$ | nA            |
| $I_{CC}$  | $V_I = V_{CC}$ or 0, $I_O = 0$                          | 6 V      |                          |           | 2         |            | 40         |            | 20         | $\mu\text{A}$ |
| $C_i$     |                                                         | 2 to 6 V |                          | 3         | 10        |            | 10         |            | 10         | pF            |



**SN54HC4002, SN74HC4002**  
**DUAL 4-INPUT POSITIVE-NOR GATES**

switching characteristics over recommended operating free-air temperature range (unless otherwise noted),  $C_L = 50 \text{ pF}$  (see Note 1)

| PARAMETER | FROM<br>(INPUT) | TO<br>(OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC4002 |     | SN74HC4002 |     | UNIT |
|-----------|-----------------|----------------|----------|--------------------------|-----|-----|------------|-----|------------|-----|------|
|           |                 |                |          | MIN                      | TYP | MAX | MIN        | MAX | MIN        | MAX |      |
| $t_{pd}$  | A thru D        | Y              | 2 V      |                          | 44  | 110 |            | 165 |            | 140 | ns   |
|           |                 |                | 4.5 V    |                          | 12  | 22  |            | 33  |            | 28  |      |
|           |                 |                | 6 V      |                          | 11  | 19  |            | 28  |            | 24  |      |
| $t_t$     |                 | Y              | 2 V      |                          | 38  | 75  |            | 110 |            | 95  | ns   |
|           |                 |                | 4.5 V    |                          | 8   | 15  |            | 22  |            | 19  |      |
|           |                 |                | 6 V      |                          | 6   | 13  |            | 19  |            | 16  |      |

|          |                                        |                                   |           |
|----------|----------------------------------------|-----------------------------------|-----------|
| $C_{pd}$ | Power dissipation capacitance per gate | No load, $T_A = 25^\circ\text{C}$ | 25 pF typ |
|----------|----------------------------------------|-----------------------------------|-----------|

Note 1: Load circuits and voltage waveforms are shown in Section 1.

**TEXAS**  
  
**INSTRUMENTS**

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

## **IMPORTANT NOTICE**

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

**TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.**

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.